

## Lacquer Thinner

### SECTION 1. IDENTIFICATION

|   |  |
|---|--|
| <b>Product Identifier</b>               | Lacquer Thinner  |
| <b>Other Means of Identification</b>    | 13-350, 13-351, 13-354, 13-358, 33-354MFSEXP, 33-808CQ, 33-854CQ, 83-851, 83-854, 83-858, 35-858CQ, 53-350, 53-351, 53-354       |
| <b>Recommended Use</b>                  | Please refer to Product label.   |
| <b>Restrictions on Use</b>              | None known.  |
| <b>Manufacturer/Supplier Identifier</b> | Recochem Inc., 850 Montee de Liesse, Montreal, QC, H4T 1P4, Compliance and Regulatory Department, 905-878-5544, www.recochem.com |
| <b>Emergency Phone No.</b>              | CANUTEC, 613-996-6666, 24 Hours  |
| <b>SDS No.</b>                          | 1632   |

### SECTION 2. HAZARD IDENTIFICATION

#### Classification

Flammable liquid - Category 2; Acute toxicity (Oral) - Category 3; Acute toxicity (Dermal) - Category 3; Acute toxicity (Inhalation) - Category 3; Skin irritation - Category 2; Eye irritation - Category 2A; Germ cell mutagenicity - Category 1B; Carcinogenicity - Category 1B; Reproductive toxicity - Category 2; Specific target organ toxicity (single exposure) - Category 1; Specific target organ toxicity (single exposure) - Category 3; Specific target organ toxicity (repeated exposure) - Category 2; Aspiration hazard - Category 1; Aquatic hazard (Acute) - Category 2

#### Label Elements



Signal Word:  
Danger

#### Hazard Statement(s):

|      |  |
|------|--|
| H225 | Highly flammable liquid and vapour.                                |
| H301 | Toxic if swallowed.  |
| H311 | Toxic in contact with skin.  |
| H331 | Toxic if inhaled.  |
| H304 | May be fatal if swallowed and enters airways.                      |
| H315 | Causes skin irritation.  |
| H319 | Causes serious eye irritation.                                     |
| H336 | May cause drowsiness or dizziness.                                 |
| H340 | May cause genetic defects.   |
| H350 | May cause cancer.  |
| H361 | Suspected of damaging fertility or the unborn child.               |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H401 | Toxic to aquatic life.   |

Precautionary Statement(s):

Prevention:

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat, sparks, open flames, and hot surfaces. – No smoking.
- P233 Keep container tightly closed.
- P241 Use explosion-proof electrical, ventilating, lighting, and other equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P260 Do not breathe fume, mist, vapours, spray.
- P264 Wash hands and skin thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P273 Avoid release to the environment.

Response:

- P301 + P310 IF SWALLOWED: Immediately call a POISON CENTRE or doctor.
- P330 Rinse mouth.
- P331 Do NOT induce vomiting.
- P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P312 Call a POISON CENTRE or doctor if you feel unwell.
- P332 + P313 If skin irritation occurs: Get medical advice/attention.
- P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P312 Call a POISON CENTRE or doctor if you feel unwell.
- P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P312 Call a POISON CENTRE or doctor if you feel unwell.
- P337 + P313 If eye irritation persists: Get medical advice/attention.
- P370 + P378 In case of fire: Use appropriate foam, carbon dioxide, dry chemical powder, water spray or fog to extinguish.

Storage:

Store in a well ventilated place. Keep cool. Keep container tightly closed. Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable regional, national and local laws and regulations.

**Other Hazards**

None known.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture:

| Chemical Name       | CAS No.  | %     | Other Identifiers | Other Names |
|---------------------|----------|-------|-------------------|-------------|
| Benzene             | 71-43-2  | 0.1-1 |                   |             |
| Acetone             | 67-64-1  | 7-13  |                   |             |
| Methyl ethyl ketone | 78-93-3  | 5-10  |                   |             |
| Methanol            | 67-56-1  | 10-30 |                   |             |
| Toluene             | 108-88-3 | 40-70 |                   |             |

Product Identifier: Lacquer Thinner - Ver. 1

SDS No.: 1632

Date of Preparation: January 04, 2016

Date of Last Revision: September 12, 2019

Page 02 of 10

|                        |           |       |  |  |
|------------------------|-----------|-------|--|--|
| Xylene (mixed isomers) | 1330-20-7 | 10-30 |  |  |
|------------------------|-----------|-------|--|--|

#### Notes

The specific chemical identity and/or exact percentage of composition (concentration) has been withheld as a trade secret.

## SECTION 4. FIRST-AID MEASURES

### First-aid Measures

#### Inhalation

Take precautions to ensure your own safety before attempting rescue (e.g. wear appropriate protective equipment). Remove source of exposure or move to fresh air. Keep at rest in a position comfortable for breathing. Immediately call a Poison Centre or doctor.

#### Skin Contact

Avoid direct contact. Wear chemical protective clothing if necessary. Take off immediately contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Quickly and gently blot or brush away excess chemical. Immediately rinse with lukewarm, gently flowing water for 15-20 minutes. Call a Poison Centre or doctor. If skin irritation occurs, get medical advice or attention. Thoroughly clean clothing, shoes and leather goods before reuse or dispose of safely.

#### Eye Contact

Avoid direct contact. Wear chemical protective gloves if necessary. Quickly and gently blot or brush chemical off the face. Immediately rinse the contaminated eye(s) with lukewarm, gently flowing water for 15-20 minutes, while holding the eyelid(s) open. Remove contact lenses, if present and easy to do. Take care not to rinse contaminated water into the unaffected eye or onto the face. If eye irritation persists, get medical advice or attention.

#### Ingestion

Rinse mouth with water. Never give anything by mouth if person is rapidly losing consciousness, or is unconscious or convulsing. Do not induce vomiting. If vomiting occurs naturally, lie on your side in the recovery position. Rinse mouth with water again. Avoid mouth-to-mouth contact by using a barrier device. Immediately call a Poison Centre or doctor.

### Most Important Symptoms and Effects, Acute and Delayed

No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

### Immediate Medical Attention and Special Treatment

#### Target Organs

Auditory (hearing) system, nervous system, skin.

#### Special Instructions

No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

#### Medical Conditions Aggravated by Exposure

None known.

## SECTION 5. FIRE-FIGHTING MEASURES

### Extinguishing Media

#### Suitable Extinguishing Media

Carbon dioxide, dry chemical powder, appropriate foam, water spray or fog.

#### Unsuitable Extinguishing Media

None known.

### Specific Hazards Arising from the Product

Highly flammable liquid and vapour. Can ignite at room temperature. Releases vapour that can form explosive mixture with air. Can be ignited by static discharge. Can accumulate static charge by flow, splashing or agitation. May travel a considerable distance to a source of ignition and flash back to a leak or open container. See Section 9 (Physical and

Product Identifier: Lacquer Thinner - Ver. 1  
Date of Preparation: January 04, 2016  
Date of Last Revision: September 12, 2019

SDS No.: 1632

Page 03 of 10

Chemical Properties) for flash point and explosive limits. May accumulate in hazardous amounts in low-lying areas especially inside confined spaces, resulting in a fire and/or health hazard. Closed containers may rupture violently when heated releasing contents.

In a fire, the following hazardous materials may be generated: toxic chemicals; very toxic carbon monoxide, carbon dioxide.

#### **Special Protective Equipment and Precautions for Fire-fighters**

Review Section 6 (Accidental Release Measures) for important information on responding to leaks/spills.

See Skin Protection in Section 8 (Exposure Controls/Personal Protection) for advice on suitable chemical protective materials.

## **SECTION 6. ACCIDENTAL RELEASE MEASURES**

### **Personal Precautions, Protective Equipment, and Emergency Procedures**

Evacuate the area immediately. Isolate the hazard area. Keep out unnecessary and unprotected personnel. Evacuate downwind locations. Do not touch damaged containers or spilled product unless wearing appropriate protective equipment. Use the personal protective equipment recommended in Section 8 of this safety data sheet. Increase ventilation to area or move leaking container to a well-ventilated and secure area. Eliminate all ignition sources. Use grounded, explosion-proof equipment. May accumulate in hazardous amounts in low-lying areas especially inside confined spaces, if ventilation is not sufficient. Distant ignition and flashback are possible.

### **Environmental Precautions**

Do not allow into any sewer, on the ground or into any waterway.

### **Methods and Materials for Containment and Cleaning Up**

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

## **SECTION 7. HANDLING AND STORAGE**

### **Precautions for Safe Handling**

Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

### **Conditions for Safe Storage**

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

## **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

Product Identifier: Lacquer Thinner - Ver. 1

SDS No.: 1632

Date of Preparation: January 04, 2016

Date of Last Revision: September 12, 2019

Page 04 of 10

**Control Parameters**

| Chemical Name          | ACGIH TLV®         |                    | OSHA PEL |          | AIHA WEEL |     |
|------------------------|--------------------|--------------------|----------|----------|-----------|-----|
|                        | TWA                | STEL               | TWA      | Ceiling  | 8-hr TWA  | TWA |
| Acetone                | 250 ppm A4         | 500 ppm A4         | 750 ppm  | 1000 ppm |           |     |
| Methyl ethyl ketone    | 200 ppm            | 300 ppm            | 200 ppm  | 300 ppm  |           |     |
| Methanol               | 200 ppm            | 250 ppm            | 200 ppm  | 250 ppm  |           |     |
| Toluene                | 20 ppm A4          | Not established    | 100 ppm  | 150 ppm  |           |     |
| Xylene (mixed isomers) | 100 ppm            | 150 ppm            | 100 ppm  | 150 ppm  |           |     |
| Benzene                | 0.5 ppm A1<br>Skin | 2.5 ppm A1<br>Skin | 1 ppm    | 5 ppm    |           |     |

**Appropriate Engineering Controls**

Do not allow product to accumulate in the air in work or storage areas, or in confined spaces. Use local exhaust ventilation, if general ventilation is not adequate to control amount in the air. Use non-sparking ventilation systems, approved explosion-proof equipment and intrinsically safe electrical systems in areas where this product is used and stored. Control static electricity discharges which includes bonding of equipment to ground. Use only non-combustible, compatible materials for walls, floors, ventilation system, air cleaning devices, pallets, shelving. Provide eyewash and safety shower if contact or splash hazard exists.

**Individual Protection Measures****Eye/Face Protection**

Wear chemical safety goggles.

**Skin Protection**

Wear chemical protective clothing e.g. gloves, aprons, boots.  
Suitable materials are: nitrile rubber.

**Respiratory Protection**

Wear a NIOSH approved air-purifying respirator with an appropriate cartridge.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES****Basic Physical and Chemical Properties**

|   |   |
|---|---|
| <b>Appearance</b>                                       | Clear liquid.   |
| <b>Odour</b>  | Hydrocarbon   |
| <b>Odour Threshold</b>                                  | 0.16 - 37 ppm (0.6 - 139.2 mg/m <sup>3</sup> ) (Toluene)                          |
| <b>pH</b>   | Not available   |
| <b>Melting Point/Freezing Point</b>                     | -95 °C (-139 °F) (Toluene) (melting); -95 °C (-139 °F) (Toluene) (freezing)       |
| <b>Initial Boiling Point/Range</b>                      | 110.6 °C (231.1 °F) (Toluene)   |
| <b>Flash Point</b>                                      | -4 °C (25 °F) (closed cup)  |
| <b>Evaporation Rate</b>                                 | 2.0 (estimated) (n-butyl acetate = 1)   |
| <b>Flammability (solid, gas)</b>                        | Not applicable  |
| <b>Upper/Lower Flammability or Explosive Limit</b>      | 36% (Methanol) (upper); 6% (Methanol) (lower)                                     |
| <b>Vapour Pressure</b>                                  | 21.98 mm Hg (2.93 kPa) at 20 °C (Toluene)   |
| <b>Vapour Density (air = 1)</b>                         | 3.18 (estimated)  |
| <b>Relative Density (water = 1)</b>                     | 0.835 - 0.839 at 20 °C  |
| <b>Solubility</b>                                       | Slightly soluble in water; Soluble in all proportions in common organic solvents. |
| <b>Partition Coefficient, n-Octanol/Water (Log Kow)</b> | Not available   |
| <b>Auto-ignition Temperature</b>                        | 385 °C (725 °F) (Methanol)  |

Product Identifier: Lacquer Thinner - Ver. 1

SDS No.: 1632

Date of Preparation: January 04, 2016

Date of Last Revision: September 12, 2019

Page 05 of 10

|                                  |   |
|----------------------------------|---|
| <b>Decomposition Temperature</b> | Not available   |
| <b>Viscosity</b>                 | 0.676 mm <sup>2</sup> /s at 25 °C (estimated) (kinematic); 0.586 mPa.s at 20 °C (estimated) (dynamic) |
| <b>Other Information</b>         |   |
| <b>Physical State</b>            | Liquid  |
| <b>Molecular Weight</b>          | Not applicable  |

## SECTION 10. STABILITY AND REACTIVITY

### Reactivity

Not reactive under normal conditions of use.

### Chemical Stability

Normally stable.

### Possibility of Hazardous Reactions

None expected under normal conditions of storage and use.

### Conditions to Avoid

High temperatures. Accumulation of static charge. Open flames, sparks, static discharge, heat and other ignition sources. Hot surfaces. Prolonged exposure to air. Acidic conditions (low pH). Temperatures above -2.0 °C (28.4 °F)

### Incompatible Materials

Reacts violently with: strong acids (e.g. hydrochloric acid). Reacts explosively with: strong oxidizing agents (e.g. perchloric acid), oxidizing agents (e.g. peroxides).

Not corrosive to metals.

### Hazardous Decomposition Products

Very toxic carbon monoxide, carbon dioxide; very toxic, flammable aldehydes; very toxic, flammable formaldehyde.

## SECTION 11. TOXICOLOGICAL INFORMATION

### Likely Routes of Exposure

Inhalation.

### Acute Toxicity

| Chemical Name          | LC50   | LD50 (oral)             | LD50 (dermal)          |
|------------------------|--|-------------------------|------------------------|
| Acetone                | 18600 ppm (male mouse)<br>(4-hour exposure)              | 5245 mg/kg (male mouse) | > 15800 mg/kg (rabbit) |
| Methyl ethyl ketone    | 11300-11700 ppm (rat)<br>(4-hour exposure)               | 2737 mg/kg (rat)        | > 8050 mg/kg (rabbit)  |
| Methanol               | 64000 ppm (rat) (4-hour<br>exposure)                     | 143 mg/kg Human - Male  | 15800 mg/kg (rabbit)   |
| Toluene                | 12500-28800 mg/m <sup>3</sup> (rat)<br>(4-hour exposure) | > 5580 mg/kg (rat)      | 12125 mg/kg (rabbit)   |
| Xylene (mixed isomers) | 6350 mg/m <sup>3</sup> (male rat)<br>(4-hour exposure)   | 3523 mg/kg (rat)        | > 1700 mg/kg (rabbit)  |
| Benzene                | 13700 ppm (rat) (4-hour<br>exposure)                     | 930 mg/kg (rat)         | 8240 mg/kg (rabbit)    |

Inhalation ATE: 16,361 mg/L 4hr

Oral ATE: 830.72 mg/kg

Dermal ATE: 7029 mg/kg

### Skin Corrosion/Irritation

Animal tests show moderate or severe irritation.

Product Identifier: Lacquer Thinner - Ver. 1  
Date of Preparation: January 04, 2016  
Date of Last Revision: September 12, 2019

SDS No.: 1632

Page 06 of 10

## Serious Eye Damage/Irritation

Human experience and animal tests show serious eye irritation. The vapour also irritates the eyes.

## STOT (Specific Target Organ Toxicity) - Single Exposure

### Inhalation

Toxic, can cause death based on human experience. At high concentrations.

### Skin Absorption

May be harmful based on limited evidence. (Toluene). (Methyl ethyl ketone). (Methanol)

### Ingestion

Toxic, can cause death based on human experience. depression of the central nervous system, impaired vision and blindness. In some cases, there may be delayed effects on the nervous system. Symptoms may include headache, nausea, vomiting, dizziness, drowsiness and confusion. A severe exposure may cause stomach pain, muscle pain, difficult breathing and coma. Vision can be impaired and permanent blindness can result. There may be other permanent effects on the nervous system e.g. tremor, seizures.

## Aspiration Hazard

May be drawn into the lungs (aspirated) if swallowed or vomited. Death can result.

## STOT (Specific Target Organ Toxicity) - Repeated Exposure

May cause If inhaled: effects on the central nervous system, "organic solvent syndrome", hearing loss, harmful effects on the hearing (auditory) system. Exposure to this chemical and loud noise may cause greater hearing loss than expected from noise exposure alone.

## Respiratory and/or Skin Sensitization

Not a respiratory sensitizer. (Toluene). (Acetone). (Methanol)

Not a skin sensitizer. (Toluene). (Acetone)

May cause an allergic reaction (skin sensitization) based on limited evidence. (Methyl ethyl ketone). (Methanol)

## Carcinogenicity

| Chemical Name          | IARC       | ACGIH®         | NTP              | OSHA       |
|------------------------|------------|----------------|------------------|------------|
| Acetone                | Not Listed | A4             | Not Listed       | Not Listed |
| Methyl ethyl ketone    | Not Listed | Not Listed     | Not Listed       | Not Listed |
| Methanol               | Not Listed | Not designated | Not Listed       | Not Listed |
| Toluene                | Group 3    | A4             | Not Listed       | Not Listed |
| Xylene (mixed isomers) | Group 3    | A4             | Not Listed       | Not Listed |
| Benzene                | Group 1    | A1             | Known carcinogen | Listed     |

## Reproductive Toxicity

### Development of Offspring

Animal studies show effects on the offspring. If inhaled: known to cause: decreased weight, long-lasting behavioural changes, hearing loss, miscarriage. (Toluene)

May cause effects on the unborn child based on limited evidence. However, these effects are only seen with significant toxicity in the mothers. If inhaled: known to cause: decreased weight. Embryotoxic (late resorptions)

Studies in people and animals show effects on the unborn child. If inhaled: has been associated with: miscarriage. (Acetone)

Animal studies show effects on the offspring. If swallowed: known to cause: teratogenic(external, soft tissue and skeletal defects) decreased weight.

### Sexual Function and Fertility

Conclusions cannot be drawn from the limited studies available. (Toluene) animal studies show effects on sexual function and/or fertility. If swallowed: has been associated with: reduced male fertility.

Studies in people show effects on sexual function and/or fertility. If inhaled: known to cause: reduced male and female fertility, effects in men and women. (Acetone). (Methyl ethyl ketone) does not cause effects on sexual function or fertility. (Methanol)

### Effects on or via Lactation

Can transfer to mother's milk.

Product Identifier: Lacquer Thinner - Ver. 1

SDS No.: 1632

Date of Preparation: January 04, 2016

Date of Last Revision: September 12, 2019

Page 07 of 10

**Germ Cell Mutagenicity**

May be mutagenic based on limited evidence.

**Interactive Effects**

No information was located.

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Acute Aquatic Toxicity**

| Chemical Name          | LC50 Fish   | EC50 Crustacea  | ErC50 Aquatic Plants | ErC50 Algae   |
|------------------------|---|---|----------------------|---------------|
| Acetone                | 8300 mg/L (Lepomis macrochirus (bluegill))                                      | Not available   |                      |               |
| Methyl ethyl ketone    | 3130-3320 mg/L (Pimephales promelas (fathead minnow); 96-hour)                  | Not available   |                      | Not available |
| Methanol               | 15400 mg/L (Lepomis macrochirus (bluegill); 96-hour)                            | 10000 mg/L (Daphnia magna (water flea); 48-hour)                      |                      |               |
| Toluene                | 7.63 mg/L (Oncorhynchus mykiss (rainbow trout); 96-hour; fresh water)           | 8 mg/L (Daphnia magna (water flea); 24 hr)                            |                      |               |
| Xylene (mixed isomers) | 13.4 mg/L (Oncorhynchus mykiss (rainbow trout); 96-hour; fresh water)           | 150 mg/L (Daphnia magna (water flea))                                 |                      |               |
| Benzene                | 32000 ug/L (Pimephales promelas (fathead minnow); 48-hour; fresh water; static) | 10000 ug/L (Daphnia magna (water flea); 48-hour; fresh water; static) |                      |               |

**Chronic Aquatic Toxicity**

| Chemical Name          | NOEC Fish   | EC50 Fish | NOEC Crustacea | EC50 Crustacea |
|------------------------|---|-----------|----------------|----------------|
| Acetone                | Not available                                       |           | Not available  |                |
| Methyl ethyl ketone    | 400 mg/L (salt water)                               |           |                |                |
| Methanol               | 7900 mg/L (Lepomis macrochirus (bluegill); 200-hrs) |           |                |                |
| Toluene                | 5.44 mg/L (Oncorhynchus mykiss (rainbow trout))     |           | Not available  |                |
| Xylene (mixed isomers) | Not available                                       |           | Not available  |                |

**Persistence and Degradability**

Product Identifier: Lacquer Thinner - Ver. 1

SDS No.: 1632

Date of Preparation: January 04, 2016

Date of Last Revision: September 12, 2019

Page 08 of 10

No information was located.

**Bioaccumulative Potential**

No information was located.

**Mobility in Soil**

No information was located.

**Other Adverse Effects**

There is no information available.

## SECTION 13. DISPOSAL CONSIDERATIONS

**Disposal Methods**

The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## SECTION 14. TRANSPORT INFORMATION

| Regulation   | UN No. | Proper Shipping Name   | Transport Hazard Class(es) | Packing Group |
|--------------|--------|------------------------|----------------------------|---------------|
| Canadian TDG | 1263   | PAINT RELATED MATERIAL | 3                          | II            |
| US DOT       | 1263   | PAINT RELATED MATERIAL | 3                          | II            |

**Environmental Hazards** Potential Marine Pollutant

**Special Precautions** Please note: In containers of 5 L (5Kg) capacity or less this product is classified as a "Limited Quantities""Consumer Commodity" under TDG regulations.  
In containers of 5 L (5Kg) capacity or less this product is classified as a "Consumer Commodity" under DOT regulations.

## SECTION 15. REGULATORY INFORMATION

**Safety, Health and Environmental Regulations**

**Canada**

**Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL)**

All ingredients are listed on the DSL/NDSL.

**USA**

**Toxic Substances Control Act (TSCA) Section 8(b)**

All ingredients are listed on the TSCA Inventory.

**Additional USA Regulatory Lists**

California Proposition 65.

## SECTION 16. OTHER INFORMATION

**SDS Prepared By** Compliance and Regulatory Department  
**Phone No.** 905-878-5544  
**Date of Preparation** January 04, 2016

Product Identifier: Lacquer Thinner - Ver. 1  
Date of Preparation: January 04, 2016  
Date of Last Revision: September 12, 2019

SDS No.: 1632

Page 09 of 10

**Date of Last Revision** September 12, 2019

**Revision Indicators** The following SDS content was changed on March 20, 2017:  
SECTION 11. TOXICOLOGICAL INFORMATION; LC50/LD50 values.  
The following SDS content was changed on July 05, 2017:  
SECTION 11. TOXICOLOGICAL INFORMATION; LC50/LD50 values.  
The following SDS content was changed on March 05, 2019:  
SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES; Flash Point.  
SECTION 1. IDENTIFICATION; Other Means of Identification.  
The following SDS content was changed on September 12, 2019:  
SECTION 1. IDENTIFICATION; Other Means of Identification.

**Additional Information** We are committed to uphold the Industry Consumer Ingredient Communication Voluntary Initiative.  
Please send us your request by visiting our website at [www.recochem.com](http://www.recochem.com).

Ingredients present (intentionally added ingredients) at a concentration of greater than one percent (1%) shall be listed in descending order of predominance. Ingredients present at a concentration of not more than one percent shall be listed but may be disclosed without respect to order of predominance.

**Disclaimer** Notice to reader: To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

---

Product Identifier: Lacquer Thinner - Ver. 1  
Date of Preparation: January 04, 2016  
Date of Last Revision: September 12, 2019

SDS No.: 1632

Page 10 of 10