



# Solvable Clear Coat Wood Preservative

## Recochem Inc.

Version No: 3.4

Safety Data Sheet according to WHMIS 2015 requirements

Issue Date: 03/19/2024

Print Date: 03/19/2024

S.GHS.CAN.EN

### SECTION 1 Identification

#### Product Identifier

Product name	Solvable Clear Coat Wood Preservative
Synonyms	53-721, 53-724
Proper shipping name	PETROLEUM DISTILLATES, N.O.S.; or PETROLEUM PRODUCTS, N.O.S. (contains Stoddard Solvent)
Other means of identification	Not Available

#### Recommended use of the chemical and restrictions on use

Relevant identified uses	Alkanes from nonane to hexadecane (an alkane with sixteen carbon atoms) are liquids of higher viscosity, less and less suitable for use in gasoline. They form instead the major part of diesel and aviation fuel. Diesel fuels are characterised by their cetane number, cetane being an old name for hexadecane. The use of a quantity of material in an unventilated or confined space may result in increased exposure and an irritating atmosphere developing. Before starting consider control of exposure by mechanical ventilation.
--------------------------	--

#### Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	Recochem Inc.
Address	8725 Holgate Crescent, Milton Ontario Canada
Telephone	1-800-361-6030 (Monday-Friday, 9 AM to - 5 PM)
Fax	Not Available
Website	<a href="http://recochem.com">recochem.com</a>
Email	sds@recochem.com

#### Emergency phone number

Association / Organisation	POISON CONTROL/ANTIPOLSON (24 heures/hours):
Emergency telephone numbers	Alberta 1-800-332-1414 British Columbia 1-800-567-8911 Manitoba 1-855-776-4766 New Brunswick 911 Newfoundland and Labrador 1-866-727-1110 Northwest Territories 1-800-332-1414 Nova Scotia and Prince Edward Island 1-800-565-8161, 1-800-332-1414 or 911
Other emergency telephone numbers	Nunavut 1-800-268-9017 Ontario 1-800-268-9017 Quebec 1-800-463-5060 Saskatchewan 1-866-454-1212 Yukon Territory 867-393-8700 United States 1-800-222-1222

### SECTION 2 Hazard(s) identification

#### Classification of the substance or mixture

Classification	Flammable Liquids Category 3, Aspiration Hazard Category 1, Sensitisation (Skin) Category 1, Serious Eye Damage/Eye Irritation Category 2A, Specific Target Organ Toxicity - Single Exposure (Narcotic Effects) Category 3, Carcinogenicity Category 2, Specific Target Organ Toxicity - Repeated Exposure Category 2, Hazardous to the Aquatic Environment Long-Term Hazard Category 2
----------------	---

#### Label elements

Hazard pictogram(s)	
Signal word	Danger

#### Hazard statement(s)

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.

Solvable Clear Coat Wood Preservative

H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

Physical and Health hazard(s) not otherwise classified

Not Applicable

Precautionary statement(s) Prevention

P201	Obtain special instructions before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe mist/vapours/spray.
P271	Use in a well-ventilated area.
P280	Wear protective gloves, protective clothing, eye protection and face protection.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/intrinsically safe equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.
P273	Avoid release to the environment.
P264	Wash all exposed external body areas thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.

Precautionary statement(s) Response

P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician/first aider.
P331	Do NOT induce vomiting.
P308+P313	IF exposed or concerned: Get medical advice/ attention.
P370+P378	In case of fire: Use alcohol resistant foam or normal protein foam to extinguish.
P302+P352	IF ON SKIN: Wash with plenty of water and soap.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER/doctor/physician/first aider/if you feel unwell.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P391	Collect spillage.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Precautionary statement(s) Storage

P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

Precautionary statement(s) Disposal

P501	Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.
------	--

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
8052-41-3.	60-80	<u>Stoddard Solvent</u>
111-84-2	1-5	<u>n-nonane</u>
95-63-6	1-5	<u>1,2,4-trimethyl benzene</u>
100-41-4	0.1-1	<u>ethylbenzene</u>
91-20-3	0.1-1	<u>naphthalene</u>
1330-20-7	0.1-1	<u>xylene</u>
12001-85-3	1-5	<u>zinc naphthenate</u>

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4 First-aid measures

## Solvable Clear Coat Wood Preservative

## Description of first aid measures

Eye Contact	<p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"><li>▶ Wash out immediately with fresh running water.</li><li>▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li><li>▶ Seek medical attention without delay; if pain persists or recurs seek medical attention.</li><li>▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li></ul>
Skin Contact	<p>If skin contact occurs:</p> <ul style="list-style-type: none"><li>▶ Immediately remove all contaminated clothing, including footwear.</li><li>▶ Flush skin and hair with running water (and soap if available).</li><li>▶ Seek medical attention in event of irritation.</li></ul>
Inhalation	<ul style="list-style-type: none"><li>▶ If fumes, aerosols or combustion products are inhaled remove from contaminated area.</li><li>▶ Other measures are usually unnecessary.</li></ul>
Ingestion	<ul style="list-style-type: none"><li>▶ <b>If swallowed do NOT induce vomiting.</b></li><li>▶ If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.</li><li>▶ Observe the patient carefully.</li><li>▶ Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.</li><li>▶ Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.</li><li>▶ Seek medical advice.</li><li>▶ Avoid giving milk or oils.</li><li>▶ Avoid giving alcohol.</li><li>▶ If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.</li></ul>

Any material aspirated during vomiting may produce lung injury. Therefore emesis should not be induced mechanically or pharmacologically. Mechanical means should be used if it is considered necessary to evacuate the stomach contents; these include gastric lavage after endotracheal intubation. If spontaneous vomiting has occurred after ingestion, the patient should be monitored for difficult breathing, as adverse effects of aspiration into the lungs may be delayed up to 48 hours.

For petroleum distillates

- In case of ingestion, gastric lavage with activated charcoal can be used promptly to prevent absorption - decontamination (induced emesis or lavage) is controversial and should be considered on the merits of each individual case; of course the usual precautions of an endotracheal tube should be considered prior to lavage, to prevent aspiration.
- Individuals intoxicated by petroleum distillates should be hospitalized immediately, with acute and continuing attention to neurologic and cardiopulmonary function.
- Positive pressure ventilation may be necessary.
- Acute central nervous system signs and symptoms may result from large ingestions of aspiration-induced hypoxia.
- After the initial episode, individuals should be followed for changes in blood variables and the delayed appearance of pulmonary oedema and chemical pneumonitis. Such patients should be followed for several days or weeks for delayed effects, including bone marrow toxicity, hepatic and renal impairment. Individuals with chronic pulmonary disease will be more seriously impaired, and recovery from inhalation exposure may be complicated.
- Gastrointestinal symptoms are usually minor and pathological changes of the liver and kidneys are reported to be uncommon in acute intoxications.
- Chlorinated and non-chlorinated hydrocarbons may sensitize the heart to epinephrine and other circulating catecholamines so that arrhythmias may occur. Careful consideration of this potential adverse effect should precede administration of epinephrine or other cardiac stimulants and the selection of bronchodilators.

for naphthalene intoxication: Naphthalene requires hepatic and microsomal activation prior to the production of toxic effects. Liver microsomes catalyse the initial synthesis of the reactive 1,2-epoxide intermediate which is subsequently oxidised to naphthalene dihydrodiol and alpha-naphthol. The 2-naphthoquinones are thought to produce haemolysis, the 1,2-naphthoquinones are thought to be responsible for producing cataracts in rabbits, and the glutathione-adducts of naphthalene-1,2-oxide are probably responsible for pulmonary toxicity. Suggested treatment regime:

- ▶ Induce emesis and/or perform gastric lavage with large amounts of warm water where oral poisoning is suspected.
- ▶ Instill a saline cathartic such as magnesium or sodium sulfate in water (15 to 30g).
- ▶ Demulcents such as milk, egg white, gelatin, or other protein solutions may be useful after the stomach is emptied but oils should be avoided because they promote absorption.
- ▶ If eyes/skin contaminated, flush with warm water followed by the application of a bland ointment.
- ▶ Severe anaemia, due to haemolysis, may require small repeated blood transfusions, preferably with red cells from a non-sensitive individual.
- ▶ Where intravascular haemolysis, with haemoglobinuria occurs, protect the kidneys by promoting a brisk flow of dilute urine with, for example, an osmotic diuretic such as mannitol. It may be useful to alkalise the urine with small amounts of sodium bicarbonate but many researchers doubt whether this prevents blockage of the renal tubules.
- ▶ Use supportive measures in the case of acute renal failure. GOSSELIN, SMITH HODGE: Clinical Toxicology of Commercial Products, 5th Ed.

## SECTION 5 Fire-fighting measures

## Extinguishing media

## Special hazards arising from the substrate or mixture

Fire Incompatibility	▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
----------------------	--

## Special protective equipment and precautions for fire-fighters

Fire Fighting	
Fire/Explosion Hazard	<ul style="list-style-type: none"><li>▶ Liquid and vapour are flammable.</li><li>▶ Moderate fire hazard when exposed to heat or flame.</li><li>▶ Vapour forms an explosive mixture with air.</li></ul> <p>Combustion products include: carbon dioxide (CO<sub>2</sub>) carbon monoxide (CO) metal oxides other pyrolysis products typical of burning organic material.</p> <p><b>Contains low boiling substance:</b> Closed containers may rupture due to pressure buildup under fire conditions.</p>

## SECTION 6 Accidental release measures

## Personal precautions, protective equipment and emergency procedures

Solvable Clear Coat Wood Preservative

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	<ul style="list-style-type: none"><li>Remove all ignition sources.</li><li>Clean up all spills immediately.</li><li>Avoid breathing vapours and contact with skin and eyes.</li></ul>
Major Spills	<ul style="list-style-type: none"><li>Clear area of personnel and move upwind.</li><li>Alert Fire Brigade and tell them location and nature of hazard.</li><li>Wear breathing apparatus plus protective gloves.</li></ul>

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

Safe handling	<p>The conductivity of this material may make it a static accumulator.. A liquid is typically considered nonconductive if its conductivity is below 100 pS/m and is considered semi-conductive if its conductivity is below 10 000 pS/m.. Whether a liquid is nonconductive or semi-conductive, the precautions are the same.. A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid.</p> <p>Even with proper grounding and bonding, this material can still accumulate an electrostatic charge. If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur.</p> <ul style="list-style-type: none"><li>Containers, even those that have been emptied, may contain explosive vapours.</li><li>Do NOT cut, drill, grind, weld or perform similar operations on or near containers.</li></ul> <p><b>Contains low boiling substance:</b></p> <p>Storage in sealed containers may result in pressure buildup causing violent rupture of containers not rated appropriately.</p> <ul style="list-style-type: none"><li>Check for bulging containers.</li><li>Vent periodically</li><li>Always release caps or seals slowly to ensure slow dissipation of vapours</li><li>Electrostatic discharge may be generated during pumping - this may result in fire.</li><li>Ensure electrical continuity by bonding and grounding (earthing) all equipment.</li><li>Restrict line velocity during pumping in order to avoid generation of electrostatic discharge (&lt;=1 m/sec until fill pipe submerged to twice its diameter, then &lt;= 7 m/sec).</li><li>Avoid all personal contact, including inhalation.</li><li>Wear protective clothing when risk of overexposure occurs.</li><li>Use in a well-ventilated area.</li></ul>
Other information	<ul style="list-style-type: none"><li>Store in original containers in approved flammable liquid storage area.</li><li>Store away from incompatible materials in a cool, dry, well-ventilated area.</li><li><b>DO NOT store in pits, depressions, basements or areas where vapours may be trapped.</b></li></ul>

Conditions for safe storage, including any incompatibilities

Suitable container	<ul style="list-style-type: none"><li>Packing as supplied by manufacturer.</li><li>Plastic containers may only be used if approved for flammable liquid.</li><li>Check that containers are clearly labelled and free from leaks.</li><li>For low viscosity materials (i) : Drums and jerry cans must be of the non-removable head type. (ii) : Where a can is to be used as an inner package, the can must have a screwed enclosure.</li><li>For materials with a viscosity of at least 2680 cSt.</li></ul>
Storage incompatibility	<p>Xylenes:</p> <ul style="list-style-type: none"><li>may ignite or explode in contact with strong oxidisers, 1,3-dichloro-5,5-dimethylhydantoin, uranium fluoride</li><li>attack some plastics, rubber and coatings</li><li>may generate electrostatic charges on flow or agitation due to low conductivity.</li><li>Vigorous reactions, sometimes amounting to explosions, can result from the contact between aromatic rings and strong oxidising agents.</li><li>Aromatics can react exothermically with bases and with diazo compounds.</li></ul> <p>For alkyl aromatics:</p> <p>The alkyl side chain of aromatic rings can undergo oxidation by several mechanisms. The most common and dominant one is the attack by oxidation at benzylic carbon as the intermediate formed is stabilised by resonance structure of the ring.</p> <ul style="list-style-type: none"><li>Following reaction with oxygen and under the influence of sunlight, a hydroperoxide at the alpha-position to the aromatic ring, is the primary oxidation product formed (provided a hydrogen atom is initially available at this position) - this product is often short-lived but may be stable dependent on the nature of the aromatic substitution; a secondary C-H bond is more easily attacked than a primary C-H bond whilst a tertiary C-H bond is even more susceptible to attack by oxygen</li><li>Monoalkylbenzenes may subsequently form monocarboxylic acids; alkyl naphthalenes mainly produce the corresponding naphthalene carboxylic acids.</li></ul>

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances	Stoddard Solvent	Stoddard solvent	100 ppm / 575	720 mg/m3 / 150 ppm	Not Available	Not Available

## Solvable Clear Coat Wood Preservative

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
			mg/m3			
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	Stoddard Solvent	Stoddard solvent	100 ppm	125 ppm	Not Available	Not Available
Canada - Manitoba Occupational Exposure Limits	Stoddard Solvent	Not Available	100 ppm	Not Available	Not Available	TLV® Basis: Eye, skin, & kidney dam; nausea; CNS impair
Canada - Prince Edward Island Occupational Exposure Limits	Stoddard Solvent	Stoddard solvent	100 ppm	Not Available	Not Available	TLV® Basis: Eye, skin, & kidney dam; nausea; CNS impair
Canada - British Columbia Occupational Exposure Limits	Stoddard Solvent	Stoddard solvent (mineral spirits)	290 mg/m3	580 mg/m3	Not Available	Not Available
Canada - Nova Scotia Occupational Exposure Limits	Stoddard Solvent	Stoddard solvent	100 ppm	Not Available	Not Available	TLV Basis: eye, skin & skidney damage; nausea; central nervous system impairment
Canada - Alberta Occupational Exposure Limits	Stoddard Solvent	Stoddard solvent	100 ppm / 572 mg/m3	Not Available	Not Available	Not Available
Canada - Northwest Territories Occupational Exposure Limits	Stoddard Solvent	Stoddard solvent	100 ppm	125 ppm	Not Available	Not Available
Canada - Quebec Permissible Exposure Values for Airborne Contaminants	Stoddard Solvent	Stoddard solvent	100 ppm / 525 mg/m3	Not Available	Not Available	Not Available
Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances	n-nonane	Nonane	200 ppm / 1,050 mg/m3	1,300 mg/m3 / 250 ppm	Not Available	Not Available
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	n-nonane	Nonane, all isomers	200 ppm	250 ppm	Not Available	Not Available
Canada - Manitoba Occupational Exposure Limits	n-nonane	Not Available	200 ppm	Not Available	Not Available	TLV® Basis: CNS impair
Canada - Prince Edward Island Occupational Exposure Limits	n-nonane	Nonane	200 ppm	Not Available	Not Available	TLV® Basis: CNS impair
Canada - British Columbia Occupational Exposure Limits	n-nonane	Nonane	200 ppm	Not Available	Not Available	Not Available
Canada - Nova Scotia Occupational Exposure Limits	n-nonane	Nonane - All isomers	200 ppm	Not Available	Not Available	TLV Basis: central nervous system impairment
Canada - Alberta Occupational Exposure Limits	n-nonane	Nonane, all isomers	200 ppm / 1050 mg/m3	Not Available	Not Available	Not Available
Canada - Northwest Territories Occupational Exposure Limits	n-nonane	Nonane, all isomers	200 ppm	250 ppm	Not Available	Not Available
Canada - Quebec Permissible Exposure Values for Airborne Contaminants	n-nonane	Nonane	200 ppm / 1050 mg/m3	Not Available	Not Available	Not Available
Canada - Nova Scotia Occupational Exposure Limits	1,2,4-trimethyl benzene	1,2,4-Trimethyl benzene	25 ppm	Not Available	Not Available	TLV Basis: central nervous system impairment; asthma; hematologic effects
Canada - Northwest Territories Occupational Exposure Limits	1,2,4-trimethyl benzene	Trimethyl benzene (mixed isomer)	25 ppm	30 ppm	Not Available	Not Available
Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances	ethylbenzene	Ethyl benzene	100 ppm / 435 mg/m3	545 mg/m3 / 125 ppm	Not Available	Not Available
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	ethylbenzene	Ethyl benzene	100 ppm	125 ppm	Not Available	T20
Canada - Manitoba Occupational Exposure Limits	ethylbenzene	Not Available	20 ppm	Not Available	Not Available	TLV® Basis: URT irr; kidney dam (nephropathy); cochlear impair; BEI
Canada - Prince Edward Island Occupational Exposure Limits	ethylbenzene	Ethyl benzene	20 ppm	Not Available	Not Available	TLV® Basis: URT irr; kidney dam (nephropathy); cochlear impair; BEI
Canada - British Columbia Occupational Exposure Limits	ethylbenzene	Ethyl benzene	20 ppm	Not Available	Not Available	Not Available
Canada - Nova Scotia Occupational Exposure Limits	ethylbenzene	Ethyl benzene	100 ppm	125 ppm	Not Available	TLV Basis: upper respiratory tract irritation; central nervous system impairment; eye irritation. BEI
Canada - Alberta Occupational Exposure Limits	ethylbenzene	Ethyl benzene	100 ppm / 434 mg/m3	543 mg/m3 / 125 ppm	Not Available	Not Available

Continued...

## Solvable Clear Coat Wood Preservative

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Canada - Northwest Territories Occupational Exposure Limits	ethylbenzene	Ethyl benzene	100 ppm	125 ppm	Not Available	Schedule R
Canada - Quebec Permissible Exposure Values for Airborne Contaminants	ethylbenzene	Ethyl benzene	20 ppm	Not Available	Not Available	C3: carcinogenic effect detected in animals
Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances	naphthalene	Naphthalene	10 ppm / 50 mg/m3	75 mg/m3 / 15 ppm	Not Available	Not Available
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	naphthalene	Naphthalene	10 ppm	15 ppm	Not Available	Skin
Canada - Manitoba Occupational Exposure Limits	naphthalene	Not Available	10 ppm	Not Available	Not Available	TLV® Basis: URT irr; cataracts; hemolytic anemia
Canada - Prince Edward Island Occupational Exposure Limits	naphthalene	Naphthalene	10 ppm	Not Available	Not Available	TLV® Basis: URT irr; cataracts; hemolytic anemia
Canada - British Columbia Occupational Exposure Limits	naphthalene	Naphthalene	10 ppm	15 ppm	Not Available	Not Available
Canada - Ontario Occupational Exposure Limits	naphthalene	Particles (Insoluble or Poorly Soluble) Not Otherwise Specified (PNOS) (Respirable fraction)	3 mg/m3	Not Available	Not Available	(R) Respirable fraction: means that size fraction of the airborne particulate deposited in the gas-exchange region of the respiratory tract and collected during air sampling with a particle size-selective device that, (a) meets the ACGIH particle size-selective sampling criteria for airborne particulate matter; and (b) has the cut point of 4 µm at 50 per cent collection efficiency.
Canada - Ontario Occupational Exposure Limits	naphthalene	Particles (Insoluble or Poorly Soluble) Not Otherwise Specified (PNOS) (Inhalable fraction)	10 mg/m3	Not Available	Not Available	(I) Inhalable fraction: means that size fraction of the airborne particulate deposited anywhere in the respiratory tract and collected during air sampling with a particle size-selective device that, (a) meets the ACGIH particle size-selective sampling criteria for airborne particulate matter; and (b) has the cut point of 100 µm at 50 per cent collection efficiency.
Canada - Nova Scotia Occupational Exposure Limits	naphthalene	Naphthalene	10 ppm	15 ppm	Not Available	TLV Basis: hemotologic effects; upper respiratory tract & eye irritation; eye damage
Canada - Alberta Occupational Exposure Limits	naphthalene	Naphthalene	10 ppm / 52 mg/m3	79 mg/m3 / 15 ppm	Not Available	1 - substance may be readily absorbed through intact skin
Canada - Northwest Territories Occupational Exposure Limits	naphthalene	Naphthalene	10 ppm	15 ppm	Not Available	Skin
Canada - Quebec Permissible Exposure Values for Airborne Contaminants	naphthalene	Naphthalene	10 ppm	Not Available	Not Available	C3: carcinogenic effect detected in animals Pc: SKIN (percutaneous): Exposure is by contact with vapours or, of probable greater significance, by direct skin contact with the substance. The cutaneous route includes mucous membranes and the eyes.
Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances	xylene	Dimethylbenzene, see Xylene - Skin	100 ppm / 435 mg/m3	650 mg/m3 / 150 ppm	Not Available	Not Available
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	xylene	Xylene (o, m-, p-isomers)	100 ppm	150 ppm	Not Available	Not Available
Canada - Manitoba Occupational Exposure Limits	xylene	Not Available	100 ppm	150 ppm	Not Available	TLV® Basis: URT & eye irr; CNS impair; BEI
Canada - Prince Edward Island Occupational Exposure Limits	xylene	Xylene (all isomers)	100 ppm	150 ppm	Not Available	TLV® Basis: URT & eye irr; CNS impair; BEI
Canada - British Columbia Occupational Exposure Limits	xylene	Xylene (o, m & p isomers)	100 ppm	150 ppm	Not Available	Not Available
Canada - Nova Scotia Occupational Exposure Limits	xylene	Xylene - Mixed isomers	100 ppm	150 ppm	Not Available	TLV Basis: upper respiratory tract & eye irritation; central nervous system impairment. BEI
Canada - Alberta Occupational Exposure Limits	xylene	Dimethylbenzene (Xylene, o, m & p isomers)	100 ppm / 434 mg/m3	651 mg/m3 / 150 ppm	Not Available	Not Available
Canada - Alberta Occupational Exposure Limits	xylene	Xylene (o-,m-,p-isomers)	100 ppm / 434 mg/m3	651 mg/m3 / 150 ppm	Not Available	Not Available
Canada - Northwest Territories Occupational Exposure Limits	xylene	Xylene (o, m-, p-isomers)	100 ppm	150 ppm	Not Available	Not Available
Canada - Quebec Permissible Exposure Values for Airborne Contaminants	xylene	Xylene (o-,m-,p- isomers)	100 ppm / 434 mg/m3	651 mg/m3 / 150 ppm	Not Available	Not Available

## Solvable Clear Coat Wood Preservative

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	zinc naphthenate	Particles (Insoluble or Poorly Soluble) Not Otherwise Specified: Respirable fraction++	3 mg/m3	6 mg/m3	Not Available	Not Available
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	zinc naphthenate	Particles (Insoluble or Poorly Soluble) Not Otherwise Specified: Inhalable fraction++	10 mg/m3	20 mg/m3	Not Available	Not Available
Canada - Ontario Occupational Exposure Limits	zinc naphthenate	Particles (Insoluble or Poorly Soluble) Not Otherwise Specified (PNOS) (Inhalable fraction)	10 mg/m3	Not Available	Not Available	(I) Inhalable fraction: means that size fraction of the airborne particulate deposited anywhere in the respiratory tract and collected during air sampling with a particle size-selective device that, (a) meets the ACGIH particle size-selective sampling criteria for airborne particulate matter; and (b) has the cut point of 100 µm at 50 per cent collection efficiency.
Canada - Ontario Occupational Exposure Limits	zinc naphthenate	Particles (Insoluble or Poorly Soluble) Not Otherwise Specified (PNOS) (Respirable fraction)	3 mg/m3	Not Available	Not Available	(R) Respirable fraction: means that size fraction of the airborne particulate deposited in the gas-exchange region of the respiratory tract and collected during air sampling with a particle size-selective device that, (a) meets the ACGIH particle size-selective sampling criteria for airborne particulate matter; and (b) has the cut point of 4 µm at 50 per cent collection efficiency.
Canada - Nova Scotia Occupational Exposure Limits	zinc naphthenate	Particles (Insoluble or Poorly Soluble) [NOS] Respirable particles	3 mg/m3	Not Available	Not Available	See Appendix B current TLV/BEI Book
Canada - Nova Scotia Occupational Exposure Limits	zinc naphthenate	Particles (Insoluble or Poorly Soluble) [NOS] Inhalable particles	10 mg/m3	Not Available	Not Available	See Appendix B current TLV/BEI Book
Canada - Alberta Occupational Exposure Limits	zinc naphthenate	Particulate Not Otherwise Regulated: Respirable	3 mg/m3	Not Available	Not Available	3 - Occupational exposure limit is based on irritation effects and its adjustment to compensate for unusual work schedules is not required.
Canada - Alberta Occupational Exposure Limits	zinc naphthenate	Particulate Not Otherwise Regulated: Total	10 mg/m3	Not Available	Not Available	3 - Occupational exposure limit is based on irritation effects and its adjustment to compensate for unusual work schedules is not required.
Canada - Northwest Territories Occupational Exposure Limits	zinc naphthenate	Particles (Insoluble or Poorly Soluble) Not Otherwise Specified: Inhalable fraction	10 mg/m3	20 mg/m3	Not Available	Not Available
Canada - Northwest Territories Occupational Exposure Limits	zinc naphthenate	Particles (Insoluble or Poorly Soluble) Not Otherwise Specified: Respirable fraction	3 mg/m3	6 mg/m3	Not Available	Not Available
Canada - Quebec Permissible Exposure Values for Airborne Contaminants	zinc naphthenate	Particulates Not Otherwise Classified (PNOC) - Total dust	10 mg/m3	Not Available	Not Available	Note 1: The standard corresponds to dust containing no asbestos and the percentage in crystalline silica is less than 1%.

## Emergency Limits

Ingredient	TEEL-1	TEEL-2	TEEL-3
Stoddard Solvent	300 mg/m3	1,800 mg/m3	29500** mg/m3
n-nonane	600 ppm	830 ppm	5,000 ppm
1,2,4-trimethyl benzene	140 mg/m3	360 mg/m3	2,200 mg/m3
1,2,4-trimethyl benzene	Not Available	Not Available	480 ppm
ethylbenzene	Not Available	Not Available	Not Available
naphthalene	15 ppm	83 ppm	500 ppm
xylene	Not Available	Not Available	Not Available





Ingredient	Original IDLH	Revised IDLH
Stoddard Solvent	20,000 mg/m3	Not Available
n-nonane	Not Available	Not Available
1,2,4-trimethyl benzene	Not Available	Not Available
ethylbenzene	800 ppm	Not Available
naphthalene	250 ppm	Not Available
xylene	900 ppm	Not Available
zinc naphthenate	Not Available	Not Available

## Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk.
----------------------------------	---

Continued...

## Solvable Clear Coat Wood Preservative

Individual protection measures, such as personal protective equipment	   
Eye and face protection	<ul style="list-style-type: none"> <li>▸ Safety glasses with side shields.</li> <li>▸ Chemical goggles, [AS/NZS 1337.1, EN166 or national equivalent]</li> <li>▸ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants.</li> </ul>
Skin protection	See Hand protection below
Hands/feet protection	<ul style="list-style-type: none"> <li>▸ Wear chemical protective gloves, e.g. PVC.</li> <li>▸ Wear safety footwear or safety gumboots, e.g. Rubber</li> </ul> <p><b>NOTE:</b></p> <ul style="list-style-type: none"> <li>▸ The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.</li> <li>▸ Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.</li> </ul>
Body protection	See Other protection below
Other protection	<ul style="list-style-type: none"> <li>▸ Overalls.</li> <li>▸ PVC Apron.</li> <li>▸ PVC protective suit may be required if exposure severe.</li> <li>▸ Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity.</li> <li>▸ For large scale or continuous use wear tight-weave non-static clothing (no metallic fasteners, cuffs or pockets).</li> <li>▸ Non sparking safety or conductive footwear should be considered.</li> </ul>

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

## SECTION 9 Physical and chemical properties

## Information on basic physical and chemical properties

Appearance	Yellow		
Physical state	Liquid	Relative density (Water = 1)	0.810 - 0.830
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	1.14
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	43	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Flammable.	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

## SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	<ul style="list-style-type: none"> <li>▸ Unstable in the presence of incompatible materials.</li> <li>▸ Product is considered stable.</li> <li>▸ Hazardous polymerisation will not occur.</li> </ul>
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7

Continued...



## Solvable Clear Coat Wood Preservative

<b>Incompatible materials</b>	See section 7
<b>Hazardous decomposition products</b>	See section 5

## SECTION 11 Toxicological information

## Information on toxicological effects

<b>Inhaled</b>	<p>The material is not thought to produce either adverse health effects or irritation of the respiratory tract following inhalation (as classified by EC Directives using animal models). Nevertheless, adverse systemic effects have been produced following exposure of animals by at least one other route and good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.</p> <p>Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo.</p> <p>Inhaling high concentrations of mixed hydrocarbons can cause narcosis, with nausea, vomiting and lightheadedness. Low molecular weight (C2-C12) hydrocarbons can irritate mucous membranes and cause incoordination, giddiness, nausea, vertigo, confusion, headache, appetite loss, drowsiness, tremors and stupor.</p> <p>Central nervous system (CNS) depression may include general discomfort, symptoms of giddiness, headache, dizziness, nausea, anaesthetic effects, slowed reaction time, slurred speech and may progress to unconsciousness. Serious poisonings may result in respiratory depression and may be fatal.</p> <p>On exposure to mixed trimethylbenzenes, some people may become nervous, tensed, anxious and have difficult breathing. There may be a reduction red blood cells and bleeding abnormalities. There may also be drowsiness.</p> <p>Concentrated nonane vapours may cause irritation of the nose and throat, headache, drowsiness, dizziness, confusion, nausea, tremors, incoordination and difficulty in breathing. Very high concentrations may cause unconsciousness and death. The odour of nitrous oxides is not easily detected.</p> <p>Inhalation of naphthalene vapour is linked with headache, loss of appetite, nausea, damage to the eyes and kidneys. According to animal testing, long term exposure may cause excessive weakness and increased salivation, weight loss, difficulty breathing, collapse, and evidence of damage to the skin, liver and lungs.</p> <p>Inhalation of high concentrations of gas/vapour causes lung irritation with coughing and nausea, central nervous depression with headache and dizziness, slowing of reflexes, fatigue and inco-ordination.</p> <p>Exposure to white spirit may cause nausea and vertigo.</p> <p>The acute toxicity of inhaled alkylbenzene is best described by central nervous system depression. These compounds may also act as general anaesthetics. Whole body symptoms of poisoning include light-headedness, nervousness, apprehension, a feeling of well-being, confusion, dizziness, drowsiness, ringing in the ears, blurred or double vision, vomiting and sensations of heat, cold or numbness, twitching, tremors, convulsions, unconsciousness, depression of breathing, and arrest.</p> <p>Headache, fatigue, tiredness, irritability and digestive disturbances (nausea, loss of appetite and bloating) are the most common symptoms of xylene overexposure. Injury to the heart, liver, kidneys and nervous system has also been noted amongst workers.</p> <p>Xylene is a central nervous system depressant</p>
<b>Ingestion</b>	<p>Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result. (ICSC13733)</p> <p>Accidental ingestion of the material may be damaging to the health of the individual.</p> <p>Ingestion of petroleum hydrocarbons can irritate the pharynx, oesophagus, stomach and small intestine, and cause swellings and ulcers of the mucous. Symptoms include a burning mouth and throat; larger amounts can cause nausea and vomiting, narcosis, weakness, dizziness, slow and shallow breathing, abdominal swelling, unconsciousness and convulsions.</p> <p>Ingestion of naphthalene and related compounds may produce abdominal cramps with nausea, vomiting, diarrhoea, headache, profuse sweating, listlessness, confusion, and in severe poisonings, coma with or without convulsions. Irritation of the bladder may also occur, producing urgency, painful urination, and the passage of brown or black urine with or without albumin or casts.</p>
<b>Skin Contact</b>	<p>Repeated exposure may cause skin cracking, flaking or drying following normal handling and use.</p> <p>Workers sensitised to naphthalene and related compounds show an inflammation of the skin with scaling and reddening. Some individuals show an allergic reaction.</p> <p>Open cuts, abraded or irritated skin should not be exposed to this material</p> <p>Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.</p> <p>The liquid may be able to be mixed with fats or oils and may degrease the skin, producing a skin reaction described as non-allergic contact dermatitis. The material is unlikely to produce an irritant dermatitis as described in EC Directives.</p> <p>The material may accentuate any pre-existing dermatitis condition</p> <p>Aromatic hydrocarbons may produce sensitivity and redness of the skin. They are not likely to be absorbed into the body through the skin but branched species are more likely to.</p> <p>This material can cause inflammation of the skin on contact in some persons.</p>
<b>Eye</b>	<p>This material can cause eye irritation and damage in some persons.</p> <p>Long term exposure to naphthalene has produced clouding of the lens (cataracts) in workers.</p> <p>Direct eye contact with petroleum hydrocarbons can be painful, and the corneal epithelium may be temporarily damaged. Aromatic species can cause irritation and excessive tear secretion.</p> <p>The vapour when concentrated has pronounced eye irritation effects and this gives some warning of high vapour concentrations. If eye irritation occurs seek to reduce exposure with available control measures, or evacuate area.</p>
<b>Chronic</b>	<p>There has been concern that this material can cause cancer or mutations, but there is not enough data to make an assessment.</p> <p>Repeated or long-term occupational exposure is likely to produce cumulative health effects involving organs or biochemical systems.</p> <p>Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population.</p> <p>Ample evidence exists from experimentation that reduced human fertility is directly caused by exposure to the material.</p> <p>Prolonged or repeated skin contact may cause drying with cracking, irritation and possible dermatitis following.</p> <p>Constant or exposure over long periods to mixed hydrocarbons may produce stupor with dizziness, weakness and visual disturbance, weight loss and anaemia, and reduced liver and kidney function. Skin exposure may result in drying and cracking and redness of the skin.</p> <p>Immersion of the hands and forearms in white spirits may quickly result in inflammation of the skin and follicles. Workers exposed to white spirit have reported nausea and vomiting and one worker has been reported to develop aplastic anaemia, bone marrow depression and this person later died from septicaemia.</p> <p>Animal testing indicates that inhalation of naphthalene may increase the incidence of respiratory tumours and may aggravate chronic inflammation.</p> <p>Women exposed to xylene in the first 3 months of pregnancy showed a slightly increased risk of miscarriage and birth defects. Evaluation of workers chronically exposed to xylene has demonstrated lack of genetic toxicity.</p> <p>Chronic solvent inhalation exposures may result in nervous system impairment and liver and blood changes. [PATTYS]</p>

Solvable Clear Coat Wood Preservative

Solvable Clear Coat Wood Preservative	TOXICITY	IRRITATION
	Not Available	Not Available
Stoddard Solvent	TOXICITY	
	Dermal (rabbit) LD50: >3000 mg/kg <sup>[1]</sup>	
	Inhalation(Rat) LC50: >5.5 mg/l4h <sup>[1]</sup>	
	Oral (Rat) LD50: >5000 mg/kg <sup>[1]</sup>	
n-nonane	TOXICITY	
	Dermal (rabbit) LD50: >2000 mg/kg <sup>[1]</sup>	
	Oral (Rat) LD50: >2000 mg/kg <sup>[1]</sup>	
1,2,4-trimethyl benzene	TOXICITY	
	Oral (Rat) LD50: 6000 mg/kg <sup>[1]</sup>	
ethylbenzene	TOXICITY	
	Dermal (rabbit) LD50: 154000 mg/kg <sup>[1]</sup>	
	Inhalation(Rat) LC50: 17.2 mg/l4h <sup>[1]</sup>	
	Oral (Rat) LD50: 3500 mg/kg <sup>[1]</sup>	
naphthalene	TOXICITY	
	dermal (rat) LD50: >2000 mg/kg <sup>[1]</sup>	
	Inhalation(Rat) LC50: >0.4 mg/l4h <sup>[1]</sup>	
	Oral (Rat) LD50: >2000 mg/kg <sup>[1]</sup>	
xylene	TOXICITY	
	Dermal (rabbit) LD50: >2000 mg/kg <sup>[1]</sup>	
	Inhalation(Rat) LC50: 17.6 mg/l/4h (approx. 4000 ppmV) <sup>[1]</sup>	
	Oral (Mouse) LD50: >2000 mg/kg <sup>[1]</sup>	
zinc naphthenate	TOXICITY	
	Oral (Rat) LD50: >2000 mg/kg <sup>[1]</sup>	
Legend:	1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances	

Solvable Clear Coat Wood Preservative	Data demonstrate that during inhalation exposure,aromatic hydrocarbons undergo substantial partitioning into adipose tissues. Following cessation of exposure, the level of aromatic hydrocarbons in body fats rapidly declines. Thus, the aromatic hydrocarbons are unlikely to bioaccumulate in the body.		
Acute Toxicity	✗	Carcinogenicity	✓
Skin Irritation/Corrosion	✗	Reproductivity	✗
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	✓
Respiratory or Skin sensitisation	✓	STOT - Repeated Exposure	✓
Mutagenicity	✗	Aspiration Hazard	✓

Legend: ✗ – Data either not available or does not fill the criteria for classification  
✓ – Data available to make classification

SECTION 12 Ecological information

Toxicity

Solvable Clear Coat Wood Preservative	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available

## Solvable Clear Coat Wood Preservative

Stoddard Solvent	Endpoint	Test Duration (hr)	Species	Value	Source
	NOEC(ECx)	3072h	Fish	1mg/l	1
	LC50	96h	Fish	2.2mg/l	4
	EC50	96h	Algae or other aquatic plants	0.277mg/l	2
	NOEC(ECx)	720h	Fish	0.02mg/l	2
	LC50	96h	Fish	0.14mg/l	2
n-nonane	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	48h	Crustacea	0.4mg/l	2
	NOEC(ECx)	504h	Crustacea	0.17mg/l	2
	LC50	96h	Fish	0.11mg/l	2
1,2,4-trimethyl benzene	Endpoint	Test Duration (hr)	Species	Value	Source
	BCF	1344h	Fish	31-207	7
	EC50	48h	Crustacea	ca.6.14mg/l	1
	EC50	96h	Algae or other aquatic plants	2.356mg/l	2
	EC50(ECx)	96h	Algae or other aquatic plants	2.356mg/l	2
	LC50	96h	Fish	3.41mg/l	2
ethylbenzene	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	96h	Algae or other aquatic plants	1.7-7.6mg/l	4
	EC50	48h	Crustacea	1.37-4.4mg/l	4
	EC50	72h	Algae or other aquatic plants	2.4-9.8mg/l	4
	EC50(ECx)	24h	Algae or other aquatic plants	0.02-938mg/l	4
	LC50	96h	Fish	3.381-4.075mg/L	4
naphthalene	Endpoint	Test Duration (hr)	Species	Value	Source
	BCF	1344h	Fish	23-146	7
	EC50	48h	Crustacea	1.09-3.4mg/l	4
	EC50	72h	Algae or other aquatic plants	ca.0.4mg/l	1
	EC50(ECx)	0.05h	Crustacea	<0.000001mg/l	4
	LC50	96h	Fish	0.213mg/l	4
xylene	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	48h	Crustacea	1.8mg/l	2
	EC50	72h	Algae or other aquatic plants	4.6mg/l	2
	NOEC(ECx)	73h	Algae or other aquatic plants	0.44mg/l	2
	LC50	96h	Fish	2.6mg/l	2
zinc naphthenate	Endpoint	Test Duration (hr)	Species	Value	Source
	LC50	96h	Fish	65.7-129mg/L	4
<b>Legend:</b> Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data					

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

For 1,2,4 - Trimethylbenzene:

Half-life (hr) air: 0.48-16;

Half-life (hr) H2O surface water: 0.24 -672;

Half-life (hr) H2O ground: 336-1344;

Half-life (hr) soil: 168-672;

Henry's Pa m3/mol: 385 -627;

Bioaccumulation: not significant. 1,2,4-Trimethylbenzene is a volatile organic compound (VOC) substance.

Atmospheric Fate: 1,2,4-trimethylbenzene can contribute to the formation of photochemical smog in the presence of other VOCs.

For Aromatic Substances Series:

Environmental Fate: Large, molecularly complex polycyclic aromatic hydrocarbons, or PAHs, are persistent in the environment longer than smaller PAHs.

Atmospheric Fate: PAHs are 'semi-volatile substances' which can move between the atmosphere and the Earth's surface in repeated, temperature-driven cycles of deposition and volatilization. Terrestrial Fate: BTEX compounds have the potential to move through soil and contaminate ground water, and their vapors are highly flammable and explosive.

Continued...

## Solvable Clear Coat Wood Preservative

For petroleum distillates:

Environmental fate:

When petroleum substances are released into the environment, four major fate processes will take place: dissolution in water, volatilization, biodegradation and adsorption. These processes will cause changes in the composition of these UVCB substances. In the case of spills on land or water surfaces, photodegradation-another fate process-can also be significant.

For Xylenes:

log Koc : 2.05-3.08; Koc : 25.4-204; Half-life (hr) air : 0.24-42; Half-life (hr) H<sub>2</sub>O surface water : 24-672; Half-life (hr) H<sub>2</sub>O ground : 336-8640; Half-life (hr) soil : 52-672; Henry's Pa m<sup>3</sup>/mol : 637-879; Henry's atm m<sup>3</sup>/mol - 7.68E-03; BOD 5 if unstated - 1.4,1%; COD - 2.56,13% ThOD - 3.125 : BCF : 23; log BCF : 1.17-2.41.

Environmental Fate: Most xylenes released to the environment will occur in the atmosphere and volatilisation is the dominant environmental fate process. Soil - Xylenes are expected to have moderate mobility in soil evaporating rapidly from soil surfaces.

For naphthalene:

Environmental Fate: Naphthalene may be reach surface water and soil through transportation in water or being carried by air. Most airborne naphthalene is in a vapour form and hence deposition is expected to be slow. A minimal amount of naphthalene emitted to the air is transported to other environmental components mostly by dry deposition.

For Petroleum Derivatives:

Environmental Fate: Chemical analysis for all individual compounds in a petroleum bulk product released to the environment is generally unrealistic due to the complexity of these mixtures and the laboratory expense. This is further complicated by differences in behavior of the substances in water, and biological/non-biological processes.

Atmospheric Fate: Petroleum derivatives with high vapor pressures are expected to evaporate and become a vapor.

**DO NOT discharge into sewer or waterways.**

### Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
n-nonane	LOW	LOW
1,2,4-trimethyl benzene	LOW (Half-life = 56 days)	LOW (Half-life = 0.67 days)
ethylbenzene	HIGH (Half-life = 228 days)	LOW (Half-life = 3.57 days)
naphthalene	HIGH (Half-life = 258 days)	LOW (Half-life = 1.23 days)
xylene	HIGH (Half-life = 360 days)	LOW (Half-life = 1.83 days)

### Bioaccumulative potential

Ingredient	Bioaccumulation
Stoddard Solvent	LOW (BCF = 159)
n-nonane	HIGH (LogKOW = 4.7613)
1,2,4-trimethyl benzene	LOW (BCF = 275)
ethylbenzene	LOW (BCF = 79.43)
naphthalene	HIGH (BCF = 18000)
xylene	MEDIUM (BCF = 740)

### Mobility in soil

Ingredient	Mobility
n-nonane	LOW (Log KOC = 934.6)
1,2,4-trimethyl benzene	LOW (Log KOC = 717.6)
ethylbenzene	LOW (Log KOC = 517.8)
naphthalene	LOW (Log KOC = 1837)


## SECTION 13 Disposal considerations

### Waste treatment methods

Product / Packaging disposal	<ul style="list-style-type: none"> <li>▶ Containers may still present a chemical hazard/ danger when empty.</li> <li>▶ Return to supplier for reuse/ recycling if possible.</li> </ul> <p>Otherwise:</p> <ul style="list-style-type: none"> <li>▶ If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.</li> <li>▶ <b>DO NOT allow wash water from cleaning or process equipment to enter drains.</b></li> <li>▶ It may be necessary to collect all wash water for treatment before disposal.</li> <li>▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.</li> <li>▶ Recycle wherever possible.</li> <li>▶ Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.</li> <li>▶ Dispose of by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or Incineration in a licensed apparatus (after admixture with suitable combustible material).</li> </ul>
------------------------------	---

## SECTION 14 Transport information

### Labels Required

	
--	---

Solvable Clear Coat Wood Preservative

Marine Pollutant	
------------------	---

Land transport (TDG)

14.1. UN number or ID number	1268		
14.2. UN proper shipping name	PETROLEUM DISTILLATES, N.O.S.; or PETROLEUM PRODUCTS, N.O.S. (contains Stoddard Solvent)		
14.3. Transport hazard class(es)	Class	3	
	Subsidiary Hazard	Not Applicable	
14.4. Packing group	III		
14.5. Environmental hazard	Environmentally hazardous		
14.6. Special precautions for user	Special provisions	91, 92, 150	
	Explosive Limit and Limited Quantity Index	5 L	
	ERAP Index	Not Applicable	

Air transport (ICAO-IATA / DGR)

14.1. UN number	1268		
14.2. UN proper shipping name	Petroleum products, n.o.s. (contains Stoddard Solvent); Petroleum distillates, n.o.s. (contains Stoddard Solvent)		
14.3. Transport hazard class(es)	ICAO/IATA Class	3	
	ICAO / IATA Subsidiary Hazard	Not Applicable	
	ERG Code	3L	
14.4. Packing group	III		
14.5. Environmental hazard	Environmentally hazardous		
14.6. Special precautions for user	Special provisions	A3	
	Cargo Only Packing Instructions	366	
	Cargo Only Maximum Qty / Pack	220 L	
	Passenger and Cargo Packing Instructions	355	
	Passenger and Cargo Maximum Qty / Pack	60 L	
	Passenger and Cargo Limited Quantity Packing Instructions	Y344	
	Passenger and Cargo Limited Maximum Qty / Pack	10 L	

Sea transport (IMDG-Code / GGVSee)

14.1. UN number	1268		
14.2. UN proper shipping name	PETROLEUM PRODUCTS, N.O.S. (contains Stoddard Solvent); PETROLEUM DISTILLATES, N.O.S. (contains Stoddard Solvent)		
14.3. Transport hazard class(es)	IMDG Class	3	
	IMDG Subsidiary Hazard	Not Applicable	
14.4. Packing group	III		
14.5 Environmental hazard	Marine Pollutant		
14.6. Special precautions for user	EMS Number	F-E , S-E	
	Special provisions	223 955	
	Limited Quantities	5 L	

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
Stoddard Solvent	Not Available
n-nonane	Not Available
1,2,4-trimethyl benzene	Not Available
ethylbenzene	Not Available
naphthalene	Not Available

Solvable Clear Coat Wood Preservative

Product name	Group
xylene	Not Available
zinc naphthenate	Not Available

14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type
Stoddard Solvent	Not Available
n-nonane	Not Available
1,2,4-trimethyl benzene	Not Available
ethylbenzene	Not Available
naphthalene	Not Available
xylene	Not Available
zinc naphthenate	Not Available

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations and the SDS contains all the information required by the Hazardous Products Regulations.

Stoddard Solvent is found on the following regulatory lists

- Canada Categorization decisions for all DSL substances
- Canada Domestic Substances List (DSL)
- Canada Toxicological Index Service - Workplace Hazardous Materials Information System - WHMIS GHS
- Chemical Footprint Project - Chemicals of High Concern List
- International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic

n-nonane is found on the following regulatory lists

- Canada Categorization decisions for all DSL substances
- Canada Domestic Substances List (DSL)
- Canada Toxicological Index Service - Workplace Hazardous Materials Information System - WHMIS GHS

1,2,4-trimethyl benzene is found on the following regulatory lists

- Canada Categorization decisions for all DSL substances
- Canada Domestic Substances List (DSL)
- Canada Toxicological Index Service - Workplace Hazardous Materials Information System - WHMIS GHS

ethylbenzene is found on the following regulatory lists

- Canada Categorization decisions for all DSL substances
- Canada Domestic Substances List (DSL)
- Canada Toxicological Index Service - Workplace Hazardous Materials Information System - WHMIS GHS
- Chemical Footprint Project - Chemicals of High Concern List
- International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs
- International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2B: Possibly carcinogenic to humans

naphthalene is found on the following regulatory lists

- Canada Categorization decisions for all DSL substances
- Canada Domestic Substances List (DSL)
- Canada Toxicological Index Service - Workplace Hazardous Materials Information System - WHMIS GHS
- Chemical Footprint Project - Chemicals of High Concern List
- International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs
- International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2B: Possibly carcinogenic to humans
- International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

xylene is found on the following regulatory lists

- Canada Categorization decisions for all DSL substances
- Canada Domestic Substances List (DSL)
- Canada Toxicological Index Service - Workplace Hazardous Materials Information System - WHMIS GHS
- International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic

zinc naphthenate is found on the following regulatory lists

- Canada Categorization decisions for all DSL substances
- Canada Domestic Substances List (DSL)
- International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

Additional Regulatory Information

Not Applicable

National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes

Solvable Clear Coat Wood Preservative

National Inventory	Status
Canada - NDSL	No (Stoddard Solvent; n-nonane; 1,2,4-trimethyl benzene; ethylbenzene; naphthalene; xylene; zinc naphthenate)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	No (zinc naphthenate)
Vietnam - NCI	Yes
Russia - FBEPH	Yes
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

SECTION 16 Other information

Revision Date	03/19/2024
Initial Date	03/21/2022

**CONTACT POINT**

IMMEDIATELY contact the local POISON CONTROL center for your area (24 hours): Alberta 1-800-332-1414 British Columbia 1-800-567-8911 Manitoba 1-855-776-4766 New Brunswick 911 Newfoundland and Labrador 1-866-727-1110 Northwest Territories 1-800-332-1414 Nova Scotia and Prince Edward Island 1-800-565-8161, 1-800-332-1414 or 911 Nunavut 1-800-268-9017 Ontario 1-800-268-9017 Quebec 1-800-463-5060 Saskatchewan 1-866-454-1212 Yukon Territory 867-393-8700 United States 1-800-222-1222 Contactez IMMÉDIATEMENT le centre ANTIPOISON de votre région (24 heures): Alberta 1-800-332-1414 Colombie-Britannique 1-800-567-8911 Manitoba 1-855-776-4766 Nouveau-Brunswick 911 Terre-Neuve-et-Labrador 1-866-727-1110 Territoires du Nord-Ouest 1-800-332-1414 Nouvelle-Écosse et Île-du-Prince-Édouard 1-800-565-8161, 1-800-332-1414 ou 911 Nunavut 1-800-268-9017 Ontario 1-800-268-9017 Québec 1-800-463-5060 Saskatchewan 1-866-454-1212 Territoire du Yukon 867-393-8700 États-Unis: 1-800-222-1222

SDS Version Summary

Version	Date of Update	Sections Updated
2.4	03/18/2024	Hazards identification - Classification

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios.

Definitions and abbreviations

- PC - TWA: Permissible Concentration-Time Weighted Average
- PC - STEL: Permissible Concentration-Short Term Exposure Limit
- IARC: International Agency for Research on Cancer
- ACGIH: American Conference of Governmental Industrial Hygienists
- STEL: Short Term Exposure Limit
- TEEL: Temporary Emergency Exposure Limit
- IDLH: Immediately Dangerous to Life or Health Concentrations
- ES: Exposure Standard
- OSF: Odour Safety Factor
- NOAEL: No Observed Adverse Effect Level
- LOAEL: Lowest Observed Adverse Effect Level
- TLV: Threshold Limit Value
- LOD: Limit Of Detection
- OTV: Odour Threshold Value
- BCF: BioConcentration Factors
- BEI: Biological Exposure Index
- DNEL: Derived No-Effect Level
- PNEC: Predicted no-effect concentration
- AIIC: Australian Inventory of Industrial Chemicals
- DSL: Domestic Substances List
- NDSL: Non-Domestic Substances List
- IECSC: Inventory of Existing Chemical Substance in China
- EINECS: European Inventory of Existing Commercial chemical Substances
- ELINCS: European List of Notified Chemical Substances
- NLP: No-Longer Polymers
- ENCS: Existing and New Chemical Substances Inventory
- KECI: Korea Existing Chemicals Inventory
- NZIoC: New Zealand Inventory of Chemicals
- PICCS: Philippine Inventory of Chemicals and Chemical Substances
- TSCA: Toxic Substances Control Act
- TCSI: Taiwan Chemical Substance Inventory
- INSQ: Inventario Nacional de Sustancias Químicas
- NCI: National Chemical Inventory
- FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances